



## 24800-ZW9-830

### Side Mount Control Box Manual Tilt Models

**BFP8D** up to S/N BAAJ1500741

**BF9.9D** up to S/N BABJ1501193

Left or right hand operation. (Control lever can be reversed.) Can be mounted in pairs. Use only with Honda outboards.

*Features:* Key switch; tilt switch; oil pressure/engine temp alert lights, emergency stop switch with lanyard, fast idle lever, 16 foot long non-detachable harness. Pigtail harness for attachment of harness "A" or instrument harness. Engine connection uses two 4-pin connectors.



## 24800-ZY1-812

### Side Mount Control Box Manual Tilt Models

**BF8D6** from S/N BAAJ1500742 and subsequent

**BF9.9D6** from S/N BABJ1501194 and subsequent

### **BF15/20D**

Left or right hand operation. (Control lever can be reversed.) Can be mounted in pairs. Use only with Honda outboards.

*Features:* Key switch; oil pressure/engine temp alert lights, emergency stop switch with lanyard, fast idle lever, 16 foot long non-detachable harness. Pigtail harness for attachment of harness "A" or instrument harness. Engine connection uses one 4-pin and one 6-pin connector.



## 24800-ZY1-874

### BF8/9.9D, BF15/20D Side Mount Control Box Power Tilt Models

Left or right hand operation. (Control lever can be reversed.) Can be mounted in pairs. Use only with Honda outboards.

*Features:* Key switch; tilt switch; oil pressure/engine temp alert lights, emergency stop switch with lanyard, fast idle lever, 16 foot long non-detachable harness. Pigtail harness for attachment of harness "A" or instrument harness. Engine connection uses one 4-pin and one 6-pin connector.



## 06240-ZV6-U00

### BF9.9/15A Side Mount Box

Left or right hand operation. (Control lever can be reversed.) Can be mounted in pairs. Use only with Honda outboards.

*Features:* Key switch; oil pressure warning light; emergency stop switch; choke/fast idle lever; neutral lock; 16 foot main wire harness.



## 24800-ZW1-040

### BF25-BF225 Side Mount Control Box

Left or right hand operation. (Control lever can be reversed). Can be mounted in pairs. Use only with Honda outboards. Contains heavier gauge wiring for increased amperage of BF225 charging circuit.

*Features:* Key switch; trim/tilt switch; oil pressure/engine temp alert lights; emergency stop switch; choke/fast idle lever; neutral lock; detachable 16 foot main wire harness (detaches at helm end). Pigtail harness for attachment of harness "A" or instrument harness.

**Suggested Retail: \$292.86**



## 24800-ZV5-020

### BF25-BF50

Same as **ZW1** control box (left) only with no trim/tilt switch.

**Suggested Retail: \$372.63**



## 24800-ZW4-H13

### BF25-BF225 Side Mount Box

Left or right hand operation. (Control lever can be reversed). Can be mounted in pairs. Use only with Honda outboards. Contains heavier gauge wiring for increased amperage of BF225 charging circuit. Use with Auto Start/EFI models.

*Features:* Key switch; trim/tilt switch; oil pressure/engine temp alert lights; emergency stop switch; neutral lock; detachable 16 foot main wire harness (detaches at control box). Pigtail harness for attachment of harness "A" or instrument harness.

**Suggested Retail: \$339.99**

# CONTROLS

Top Mount

# HONDA MARINE



**06240-ZW5-U40**

## **BF8-BF225 Premium Single Top Mount Control**

Right hand operation. For use with Honda outboards only.

*Features:* Single shift and throttle lever; fast idle function; trim and tilt switch.



**06240-ZW5-U60**

## **BF8-BF225 Premium Dual Top Mount Control**

Right hand operation. For use with Honda outboards only.

*Features:* Single shift and throttle lever for each engine; fast idle function; trim and tilt switch.



**06240-ZW5-U50**

## **BF8-BF225 Premium Single Top Mount Control**

Left hand operation. For use with Honda outboards only.

*Features:* Single shift and throttle lever; fast idle function; trim and tilt switch.



**06240-ZW5-U70**

## **BF8-BF225 Premium Dual Top Mount Control**

Left hand operation. For use with Honda outboards only.

*Features:* Single shift and throttle lever for each engine; fast idle function; trim and tilt switch.



**24800-ZW7-V31**

## **BF8-BF225 Single Top Mount Control-S Series**

Left or right hand operation. (Lever can be reversed.)

*Features:* Single shift and throttle lever; fast idle function; trim and tilt switch.

*Includes:* Start in gear protection.



**24800-ZW7-V41**

## **BF8-BF225 Dual Top Mount Control-S Series**

Left or right hand operation. (Levers can be reversed.)

*Features:* Single shift and throttle lever for each engine; fast idle function; trim and tilt switch.

*Includes:* Start in gear protection.

**NOTE: WE RECOMMEND TELEFLEX TFXTREME CABLES.  
NOTE: ALL CONTROLS USE 3300/33C UNIVERSAL CABLES.**



## 06241-ZW5-U00

### Premium Single Top Mount Control Spacer

*Features:* Provides 1 inch of lift for handle clearance with Honda premium single top mount control. Includes mounting hardware.



## 06241-ZW5-U10

### Premium Dual Top Mount Control Spacer

*Features:* Provides 1 inch of lift for handle clearance with Honda premium dual top mount control. Includes mounting hardware.



## 90443-ZW1-000AH

### S Series—Single Top Mount Control Spacer

*Features:* Provides 1 inch of lift for handle clearance with S series single top mount control. Includes mounting hardware.



## 90444-ZW1-000AH

### S Series—Dual Top Mount Control Spacer

*Features:* Provides 1 inch of lift for handle clearance with S series dual top mount control. Includes mounting hardware.

# CONTROLS

Flush Mount

**HONDA**  
**MARINE**



## 06240-ZW7-U00

### BF25-BF225 Premium Panel/ Flush Mount Control

Left or right hand operation. For use with Honda outboards only.

*Features:* Single shift and throttle lever; fast idle function; trim and tilt switch.



## 24800-ZW7-V51

### BF25-BF225 Panel/Flush Mount Control—S Series

Left or right hand operation. (Lever can be reversed).

*Features:* Single shift and throttle lever; fast idle function; trim and tilt switch; emergency stop switch; neutral lock.

*Includes:* Start in gear protection.

**NOTE: WE RECOMMEND TELEFLEX TFXTREME CABLES.**

**NOTE: ALL CONTROLS USE 3300/33C UNIVERSAL CABLES.**